



US006501593B2

(12) **United States Patent**
Akasaka et al.

(10) **Patent No.:** **US 6,501,593 B2**
(45) **Date of Patent:** ***Dec. 31, 2002**

(54) **RAMAN AMPLIFIER, OPTICAL REPEATER,
AND RAMAN AMPLIFICATION METHOD**

(75) Inventors: **Yuuichi Akasaka; Yoshihiro Emori;
Shu Namiki**, all of Chiyoda-ku (JP)

(73) Assignee: **The Furukawa Electric Co., Ltd.**,
Tokyo (JP)

(*) Notice: This patent issued on a continued prosecution application filed under 37 CFR 1.53(d), and is subject to the twenty year patent term provisions of 35 U.S.C. 154(a)(2).

Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/886,211**

(22) Filed: **Jun. 22, 2001**

(65) **Prior Publication Data**

US 2002/0085267 A1 Jul. 4, 2002

Related U.S. Application Data

(63) Continuation of application No. 09/527,748, filed on Mar. 17, 2001, now Pat. No. 6,292,288, which is a continuation-in-part of application No. PCT/JP99/03944, filed on Jul. 23, 1999.

(30) **Foreign Application Priority Data**

Jul. 23, 1998	(JP)	10-208450
Jul. 27, 1998	(JP)	10-210822
Feb. 12, 1999	(JP)	11-034769
Feb. 12, 1999	(JP)	11-034833
Jan. 14, 2000	(JP)	2000-006567

(51) Int. Cl.⁷ **H01S 3/00; G02F 1/35**

(52) U.S. Cl. **359/341.31; 359/334; 359/345; 372/3; 372/6; 372/71**

(58) Field of Search **359/334, 345, 359/341.31, 341.32, 341.33; 372/3, 6, 71**

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,805,977 A * 2/1989 Tanura et al. 359/334

(List continued on next page.)

FOREIGN PATENT DOCUMENTS

WO 01/51986 * 7/2001

OTHER PUBLICATIONS

Emori et al, Electronics Letters, vol. 34, #22, pp. 2145-2146, Oct. 29, 1998.*

(List continued on next page.)

Primary Examiner—Nelson Moskowitz

(74) *Attorney, Agent, or Firm*—Oblon, Spivak, McClelland, Maier & Neustadt, P.C.

(57) **ABSTRACT**

A Raman amplifier according to the present invention comprises a plurality of pumping means using semiconductor lasers of Fabry-Perot, DFB, or DBR type or MOPAs, and pumping lights outputted from the pumping means have different central wavelengths, and interval between the adjacent central wavelength is greater than 6 nm and smaller than 35 nm. An optical repeater according to the present invention comprises the above-mentioned Raman amplifier and adapted to compensate loss in an optical fiber transmission line by the Raman amplifier. In a Raman amplification method according to the present invention, the shorter the central wavelength of the pumping light the higher light power of said pumping light. In the Raman amplifier according to the present invention, when a certain pumping wavelength is defined as a first channel, and second to n-th channels are defined to be arranged with an interval of about 1 THz toward a longer wavelength side, the pumping lights having wavelengths corresponding to the first to n-th channels are multiplexed, and a pumping light having a wavelength spaced apart from the n-th channel by 2 THz or more toward the longer wavelength side is combined with the multiplexed light, thereby forming the pumping light source. The pumping lights having wavelengths corresponding to the channels other than (n-1)-th and (n-2)-th channels may be multiplexed, thereby forming the pumping light source. The pumping lights have wavelengths corresponding to the channels than (n-2)-th and (n-3)-th channels may be multiplexed, thereby forming the pumping light source.

51 Claims, 66 Drawing Sheets

